

YORK® YH2E

Split System Heat Pump

14.3 SEER2/7.5 HSPF2 | 1.5 to 5 tons



Next-level efficiency for now and the future

The YORK® YH2E Heat Pump provides the next grade of efficiency in an entry-level model with its 14.3 SEER2 cooling efficiency and high EER2 performance required in southern US climates. Expertly designed and engineered, and rigorously tested, these YH2E Heat Pumps offer the latest in energy savings and lasting performance for years to come.

Designed and constructed for optimal installation, performance and serviceability

- Meets new updated DOE 2023 minimum standards
- Durable powder-coating painted finish
- Low-sound fan design
- Easy installation and serviceability


Heat pumps and air conditioners

A heat pump (HP) is a high-performance air conditioner (AC) that also provides heat by using a valve to reverse the refrigeration cycle. Unlike typical AC units, heat pumps leverage the heat produced through the refrigeration cycle to heat the home. This can help offset the reliance on natural gas for heat and save money.

14.3 SEER2
1.5 to 5 tons



14.3 SEER2 can save you up to 40% on energy bills*



* The percentage savings are calculated based on the \$0.14/kWh national average for three-ton 8 SEER versus 14.3 SEER2 units.

Quality design and construction

1. Designed for optimal performance in southeastern and southwestern US regions (meets DOE 2023 minimum requirements).
2. Aluminum alloy micro-channel coils for maximum efficiency and durability.
3. Extruded louver for extra strength.
4. Automotive-grade powder-coating painted finish with industry-leading 1,000-hour salt-spray rating.
5. Unique low-sound fan design.
6. Eco-friendly: CFC-free R-410A refrigerant delivers environmentally friendly performance with zero ozone depletion.

Industry's most serviceable unit

7. Streamlined footprint for easier transportation and installation.
8. Removeable fan guard.
9. Swing-out control box.
10. Full access from the top and side.



SKU	Tonnage	Voltage	Liquid line (inches)	Suction line (inches)	Dimensions (inches)			Sound dBA	Approximate operating weight (lbs)
					H	W	D		
YH2E18SB21S	1.5	208-230V	3/8	3/4	30	29 1/4	29 1/4	73	150
YH2E24TB21S	2.0	208-230V	3/8	3/4	30	29 1/4	29 1/4	73	150
YH2E30TB21S	2.5	208-230V	3/8	3/4	36 1/4	29 1/4	29 1/4	73	165
YH2E36TB21S	3.0	208-230V	3/8	3/4	33 1/4	35 1/4	31 3/4	73	185
YH2E42TB21S	3.5	208-230V	3/8	7/8	36 1/4	35 1/4	31 3/4	73	215
YH2E48TB21S	4.0	208-230V	3/8	7/8	33 1/4	35 1/4	31 3/4	76	210
YH2E60TB21S	5.0	208-230V	3/8	1 1/8	36 1/4	38	34 1/4	76	230



Lower cost of ownership

14.3 SEER2 cooling efficiency can save energy costs compared to older units, and quality engineering reduces repairs to save you money.



Quiet operation

Direct-drive fan design minimizes vibration and sound.



Confidence guaranteed

Industry-leading Warranties ensure years of dependability.



Trusted quality

Manufacturer-backed Warranty: Our industry-best Warranty protection provides peace of mind.



*All Warranties require online registration within 90 days of installation. Otherwise, Warranties revert to the 5-Year Compressor Limited Warranty or the 5-Year Parts Limited Warranty.



Replacing a full system? Pair with a YORK JHET Single-Piece or JMET Modular Air Handler Unit or furnace for optimal performance.



Since 1909, this seal has signified that a product has been tested and approved by the Good Housekeeping Research Institute and is guaranteed by Good Housekeeping magazine's trusted Consumer Policy.

Visit www.york.com for more information.

YORK is a trademark of Johnson Controls. ©2022 Johnson Controls. All rights reserved. PUBL-9684-A-0822